

| REF. | | | | |
|-------|-----------|---------|---------------------|-----|
| 14967 | 3.000 Kg. | 500 Kg. | 230/400 - 3ph 50Hz. | 20" |

* Monofásico opcional



- Disponibilidad de kit móvil.
- Mobile Kit available.
- Kit de mobilité disponible.

- Altura mínima solo 95 mm, ideal para coches deportivos.
- Minimum height of just 95mm, ideal for sports cars.
- Hauteur minimum 95mm seulement, idéal pour des voitures sportives.



- Pasarelas y base Galvanizadas, extensible hasta 2.000 mm.
- Galvanized Platforms and base, extending platform up to 2.000 mm.
- Plateaux et chassis Galvanisés, extensible jusque 2.000 mm.

- Sistema hidráulico con 4 cilindros, mayor potencia.
- 4 cylinders hydraulic circuit, more powerful.
- Système hydraulique á 4 vérins, plus puissante.

- Válvula de control de bajada y sobrecarga.
- Descend and overload control valve.
- Valve de contrôle de descente et de surcharge.

- Señal acústica para descenso final.
- Acoustic signal for final descent.
- Signal sonore de descente finale.

- 4 tacos de goma incluidos.
- 4 rubber pads included.
- 4 taquets en caoutchouc de série.

- No precisa aire gracias a su doble circuito hidráulico de seguridad.
- No need of compressed aire, thanks to its double hydraulic circuit.
- Pas besoin d'aire comprimé grace a son double système hydraulic .

