

DOUBLE SCISSORS LIFT



EVO II Onground or inground

Model	Ref.	<mark>∕kg∖</mark> † †	Ŕ	∳Min ∳	\$
Onground version	13.164 + 44.730	3.000 Kg.	800 Kg.	105 mm.	230/400 V./50Hz / 3 ph
Inground version	13.164 + 44.731	3.000 Kg.	800 Kg.	—	230/400 V./50Hz / 3 ph



DOUBLE SCISSORS LIFT EVO II



Variator kit:

Refs.:

13164 + 44.730 13164 + 44.731

> Transforms a 3Ph-380V lift into a **1Ph-220V.** The lift maintains its full lifting capacity.



Simplified and reliable electric system.





Certified 🖗

REPAIRABLE

CASCOS

 (\mathbf{Z})

Double independent hydraulic system with 4 crossed cylinders: 2 masters and 2 slaves. Double hydraulic security. No need of compressed air. Very solid structure and base "solid profiles".

Repairable during at least 10 years. We ensure spare parts availability during at least this period.



www.cascos.es





CASCOS MAQUINARIA, S.A. Zurrupitieta, 8 - Pol. Ind. Júndiz • Apartado 264 01015 VITORIA-GASTEIZ / España/Spain Tel. +34 945 290 294 / Fax +34 945 290 055 e-mail: info@cascos.es

THE PLANS AND PHOTOGRAPHS SHOWN IN THIS BROCHURE ARE FOR ILLUSTRATIVE PURPOSES ONLY, AND CM RESERVES THE RIGHT FROM TIME TO TIME TO MAKE MODIFICATIONS.